


SOLVIT-PREMIUM ONE WAY VISION 7 MIL

EXTERIOR MOUNT PERFORATED VINYL

PREMIUM PRODUCT



APPLICATIONS

Short & Medium-Term Advertising Graphics on

- Vehicles
- Shop Windows
- Airport Graphics
- Glass Walls / Windows
- Bus Shelters
- Retail Signage
- Any other even transparent surface

INK COMPATIBILITY

- Solvent
- Eco Solvent
- UV
- Latex

CONTACT

4S Graphics, Inc.
764 NW 57th Court
Fort Lauderdale FL 33309
United States of America

Phone:
+1 (954) 493.6484

Website:
www.4sgraphics.com/wide-format

PRODUCT DETAILS

- Base : Calendered PVC – Perforated
- Back : Black-Black.
- Surface Finish : Gloss Finish
- Thickness : 160 microns / 7 mil
- Release Liner : Embossed & Double PE Coated paper – 140 gsm
- Perforation Ratio : 50/50, 60/40 & 70/30
- Ink Compatibility : Eco Solvent, UV & Latex Inks
- Adhesive : Acrylic, Solvent Based Permanent Adhesive
- Removability : Residue-less, if removed within 1 year.
- Ink Limit : up to 270% with Eco-Solvent Inks
- Length of Rolls : 100 Feet

PERFORATION RATIOS

50/50 – 1.5mm (0.06") perforations with Release Liner (50% Perforated 50% Retained Vinyl)

- Sizes Available: 38" x 100 Feet, 54" x 100 Feet

60/40 – 1.6mm (0.062") perforations with Release Liner (40% Perforated 60% Retained Vinyl)

- Sizes Available: 54" x 100 Feet

70/30 – 1.4mm (0.055") perforations with Release Liner (30% Perforated 70% Retained Vinyl)

- Sizes Available: 38" x 100 Feet, 54" x 100 Feet, 60" x 100 Feet

TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	RESULTS
Dimensional Stability	FINAT TM 14	Adhered to glass, no Shrinkage in cross direction, in length 0.3mm max.
Temperature Resistance		Adhered to glass -20°C to +65° C, no variation
Sea Water Resistance	DIN 50021	Adhered to Glass, after 48h/23°C no variation.
Adhesive Strength	FINAT TM 1	After 24h Stainless Steel, 4-6N/25mm
Tensile Strength		
along	DIN EN ISO 527	Min. 5 Mpa
across	DIN EN ISO 527	Min. 5 Mpa
Elongation at Break		
along	DIN EN ISO 527	Min 50%
across	DIN EN ISO 527	Min 50%
Application Temperature	Clean Dry Surface	50° – 70° F